SAFETY DATA SHEET

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Product identifier

Product name DONGWHA CCA TREATED TIMBER

Synonyms CCA TREATED TIMBER • COPPER CHROME ARSENATE TREATED TIMBER

1.2 Uses and uses advised against

Uses BUILDING APPLICATIONS • LANDSCAPING TIMBER • TIMBER

1.3 Details of the supplier of the product

Supplier name	DONGWHA AUSTRALIA PTY LTD
Address	1 Sandy Lane, Bombala, NSW, 2632, AUSTRALIA
Telephone	02 6459 5555
Fax	02 6458 3756
Website	www.dongwha.com

1.4 Emergency telephone numbers

Emergency 02 6459 5555

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

NOT CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

Physical Hazards

Not classified as a Physical Hazard

Health Hazards Not classified as a Health Hazard

Environmental Hazards

Aquatic Toxicity (Acute): Category 3 Aquatic Toxicity (Chronic): Category 3

2.2 GHS Label elements

Signal word

Pictograms

Hazard statements	
H402	Harmful to aquatic life.
H412	Harmful to aquatic life with long lasting effects.

Prevention statements

P273

Avoid release to the environment.

Response statements

None allocated.

Storage statements

None allocated.

Disposal statements P501

Dispose of contents/container in accordance with relevant regulations.

ChemAlert.

2.3 Other hazards

No information provided.

3. COMPOSITION/ INFORMATION ON INGREDIENTS

3.1 Substances / Mixtures

Ingredient	CAS Number	EC Number	Content
CHROMIUM	7440-47-3	231-157-5	<0.8%
COPPER	7440-50-8	231-159-6	<0.5%
ARSENIC	7440-38-2	231-148-6	<0.1%
TIMBER (SOFTWOOD/HARDWOOD)	-	-	>98%

4. FIRST AID MEASURES

4.1 Description of first aid measures

Eye	Exposure is considered unlikely.
Inhalation	Due to product form / nature of use, an inhalation hazard is not anticipated (unless sanding and creating wood dust).
Skin	Due to product form, acute skin hazards are not anticipated. If irritation occurs, seek medical advice.
Ingestion	For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). Due to product form and application, ingestion is considered unlikely.
First aid facilities	Eye wash facilities should be available.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Immediate medical attention and special treatment needed

Treat symptomatically.

5. FIRE FIGHTING MEASURES

5.1 Extinguishing media

Water spray or fog, for large quantities. Prevent contamination of drains and waterways.

5.2 Special hazards arising from the substance or mixture

Combustible. May evolve toxic gases (carbon/ chromium/ arsenic/ copper oxides) when heated to decomposition. Dust may form explosive mixtures with air.

5.3 Advice for firefighters

Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

5.4 Hazchem code

None allocated.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS.

6.2 Environmental precautions

Prevent product from entering drains and waterways.

6.3 Methods of cleaning up

If spilt, collect and reuse where possible.

6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.



7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

7.2 Conditions for safe storage, including any incompatibilities

Store in a cool, dry area.

7.3 Specific end uses

No information provided.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Exposure standards

Ingradiant	Reference	TWA		STEL	
Ingredient	Reference	ppm	mg/m³	ppm	mg/m³
Arsenic & soluble compounds	SWA [Proposed]		0.01		
Arsenic & soluble compounds (as As)	SWA [AUS]		0.05		
Chromium Metal	SWA [AUS]		0.5		
Copper (fume)	SWA [AUS]		0.2		
Copper (fume, dusts & mists)	SWA [Proposed]		0.01		
Copper, dusts & mists (as Cu)	SWA [AUS]		1		
Wood dust (certain hardwoods such as beech & oak)	SWA [AUS]		1		
Wood dust (soft wood)	SWA [AUS]		5		10

Biological limits

Ingredient	Determinant	Sampling Time	BEI
ARSENIC	Inorganic arsenic plus methylated metabolites in urine	End of workweek	35 μg As/L
CHROMIUM	Total chromium in urine	End of shift at end of workweek	25 µg/L
	Total chromium in urine	Increase during shift	10 µg/L

Reference: ACGIH Biological Exposure Indices

8.2 Exposure controls

Engineering controls

Avoid inhalation. Use in well ventilated areas. If sanding, drilling or cutting, use appropriate local extraction ventilation.

PPE

Eye / Face	Wear dust-proof goggles.
Hands	Wear leather or cotton gloves.
Body	Not required under normal conditions of use.
Respiratory	If cutting or sanding with potential for dust generation, wear a Class P1 (Particulate) respirator.



9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties Appearance GREY/GREEN SOLID



9.1 Information on basic physical and chemical properties

normation on saolo physical a	na ononnoar proport
Odour	ODOURLESS
Flammability	COMBUSTIBLE
Flash point	NOT AVAILABLE
Boiling point	NOT AVAILABLE
Melting point	NOT AVAILABLE
Evaporation rate	NOT AVAILABLE
рН	NOT AVAILABLE
Vapour density	NOT AVAILABLE
Specific gravity	NOT AVAILABLE
Solubility (water)	INSOLUBLE
Vapour pressure	NOT AVAILABLE
Upper explosion limit	NOT AVAILABLE
Lower explosion limit	NOT AVAILABLE
Partition coefficient	NOT AVAILABLE
Autoignition temperature	NOT AVAILABLE
Decomposition temperature	NOT AVAILABLE
Viscosity	NOT AVAILABLE
Explosive properties	NOT AVAILABLE
Oxidising properties	NOT AVAILABLE
Odour threshold	NOT AVAILABLE

10. STABILITY AND REACTIVITY

10.1 Reactivity

Carefully review all information provided in sections 10.2 to 10.6.

10.2 Chemical stability

Stable under recommended conditions of storage.

10.3 Possibility of hazardous reactions

Polymerization is not expected to occur.

10.4 Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

10.5 Incompatible materials

Compatible with most commonly used materials.

10.6 Hazardous decomposition products

May evolve toxic gases (carbon/ chromium/ arsenic/ copper oxides) when heated to decomposition.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity This product is expected to be of low acute toxicity. Under normal conditions of use, adverse health effects are not anticipated. However, this product may present a hazard if wood is sanded, drilled or cut with dust generation.

Information available for the ingredients:

Ingredient	Oral LD50	Dermal LD50	Inhalation LC50
CHROMIUM	> 5000 mg/kg (rat)		> 5.41 mg/L/4hrs (rat)
COPPER		> 2000 mg/kg (rat)	
ARSENIC	145 mg/kg (mice)		

Skin Not classified as a skin irritant. Prolonged or repeated exposure to dust may result in mechanical irritation and dermatitis.

Not classified as an eye irritant. Due to product form and nature of use, the potential for exposure is reduced. Product may only present a hazard if wood is cut or sanded with dust generation, which may result in lacrimation and irritation.

Sensitisation Not classified as causing skin or respiratory sensitisation. However, some sensitive individuals may exhibit an allergic response, possibly due to trace amounts of chromium.



Eye

Mutagenicity	Arsenic is suspected of causing genetic defects. However, due to trace levels present, adverse health effects are not anticipated.
Carcinogenicity	Not classified as a carcinogen. However, repeated exposure to wood dust may result in nasal and paranasal sinus cancers (IARC Group 1). Adverse health effects are usually associated with long-term exposure to high dust levels. Arsenic and chromium are classified as carcinogenic to humans (IARC Group 1), however due to the nature of the product and trace amounts present, adverse effects are reduced.
Reproductive	Insufficient data available to classify as a reproductive toxin.
STOT - single exposure	Not classified as causing organ damage from single exposure. Due to product form and nature of use, the potential for exposure is reduced. An inhalation hazard is not anticipated unless cut, drilled or sanded with dust generation, which may result in irritation of the nose and throat.
STOT - repeated exposure	Not classified as causing organ damage from repeated exposure. However, arsenic is a cumulative poisons, and symptoms are often delayed.
Aspiration	Not classified as causing aspiration.

12. ECOLOGICAL INFORMATION

12.1 Toxicity

Harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability

No information provided.

12.3 Bioaccumulative potential

No information provided.

12.4 Mobility in soil

No information provided.

12.5 Other adverse effects

No information provided.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Waste disposal Dispose of to an approved landfill or waste processing site. Contact the manufacturer/supplier for additional information (if required).

Legislation Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE, IMDG OR IATA

	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
14.1 UN Number	None allocated.	None allocated.	None allocated.
14.2 Proper Shipping Name	None allocated.	None allocated.	None allocated.
14.3 Transport hazard class	None allocated.	None allocated.	None allocated.
14.4 Packing Group	None allocated.	None allocated.	None allocated.

14.5 Environmental hazards

Not a Marine Pollutant

14.6 Special precautions for user

Hazchem code None allocated.

15. REGULATORY INFORMATION

ChemAlert.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Poison schedule A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

Classifications Safework Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals.

Inventory listings AUSTRALIA: AICS (Australian Inventory of Chemical Substances) All components are listed on AICS, or are exempt.

16. OTHER INFORMATION

Additional information AF

ARSENIC EXPOSURE: Acute arsenic ingestion generally produces symptoms within 30 to 60 minutes, but onset may be delayed for several hours if ingested with food. A metallic or garlic taste, vomiting, abdominal pain, dysphagia, and profuse watery (rice-like) and sometimes bloody diarrhoea may occur. Dehydration, intense thirst, & fluid-electrolyte disturbances are common. Hypovolemia from capillary leaking ("third spacing" of fluids) is a common early sign. Systemic arsenic poisoning from occupational exposure is uncommon. Arsenic workers have developed a hoarse voice, nasal irritation and possible perforation of the nasal septum, irritation of eyes, skin, and mucous membranes, and rarely, cirrhosis of the liver. Nausea and vomiting are infrequent. Painful ulceration of the wrist and scrotal skin, lips, and nostrils may develop with dust exposure. The primary target organs initially are the gastrointestinal tract, heart, brain, and kidneys. Eventually the skin, bone marrow, and peripheral nervous system may be significantly damaged. The peripheral neuropathy appears similar regardless of the route of exposure.

RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as form of product, method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: form of product; frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.



Abbreviations	ACGIH	American Conference of Governmental Industrial Hygienists
	CAS #	Chemical Abstract Service number - used to uniquely identify chemical compounds
	CNS	Central Nervous System
	EC No.	EC No - European Community Number
	EMS	Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods)
	GHS	Globally Harmonized System
	GTEPG	Group Text Emergency Procedure Guide
	IARC	International Agency for Research on Cancer
	LC50	Lethal Concentration, 50% / Median Lethal Concentration
	LD50	Lethal Dose, 50% / Median Lethal Dose
	mg/m³	Milligrams per Cubic Metre
	OEL	Occupational Exposure Limit
	рН	relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).
	ppm	Parts Per Million
	STEL	Short-Term Exposure Limit
	STOT-RE	Specific target organ toxicity (repeated exposure)
	STOT-SE	Specific target organ toxicity (single exposure)
	SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
	SWA	Safe Work Australia
	TLV	Threshold Limit Value
	TWA	Time Weighted Average
Report status		It has been compiled by RMT on behalf of the manufacturer, importer or supplier of the erves as their Safety Data Sheet ('SDS').
	manufacturer, the current sta at the time of	on information concerning the product which has been provided to RMT by the importer or supplier or obtained from third party sources and is believed to represent ate of knowledge as to the appropriate safety and handling precautions for the product f issue. Further clarification regarding any aspect of the product should be obtained he manufacturer, importer or supplier.
	does not prov accepts no li	as taken all due care to include accurate and up-to-date information in this SDS, it vide any warranty as to accuracy or completeness. As far as lawfully possible, RMT ability for any loss, injury or damage (including consequential loss) which may be curred by any person as a consequence of their reliance on the information contained
Prepared by	Risk Manager 5 Ventnor Ave Western Austr Phone: +61 8 Fax: +61 8 93 Email: info@rn Web: www.rm	ralia 6005 9322 1711 22 1794 mt.com.au

[End of SDS]

